

Request For Quote Request for Drawings Order, PO # _____

Fax this completed order form to: **(323) 762-1780 - Please photocopy this form as needed.**

Advantage Home Elevator, 2230 N. W. 12th Street, Richmond, IN 47374 (888) 877-4762 - Email: sales@advantagehomeelevator.com

Company: _____ Telephone: () _____

Contact: _____ Fax: () _____

Date: _____ Email: _____

Telephone: () _____

Fax: () _____

Date Required: _____

Job Name: _____

Elevator Type: Hydraulic MRL

Cab Size: 36" x 48" x 84" Other: _____

Rail Position: Right* Left* Forward*

* As viewed from the lowest landing looking into hoistway.

Door Strike: Right @ floor: 1 2 3 4

Left @ floor: 1 2 3 4

Gate Strike: Primary Opening Right Left

Rear or 90° Opening Right Left

Capacity: 950 lbs. (std) 750 lbs. 700 lbs.

Total travel"

Total number of landings

Total number of front openings

Total number of rear/90° openings

Pit depth (8" minimum)"

Overhead distance:"

(Minimum code req. overhead distance 99" hydro/110" MRL for 84" cab)

Walls & Ceiling:

Flat unfinished hardwood veneer panels:

Birch (std) Oak (std) Maple (std)

Cherry (opt) Mahogany (opt) Alder (opt)

Hickory (opt) Walnut (opt)

Optional upgrade unfinished recessed wall panels with matching ceiling: (Choose species from veneers above)

Optional upgrade unfinished raised wall panels with matching ceiling: (Choose species from veneers above)

Optional flat laminate wall panels:

Antique White Black Desert Glow

First Light Natural Oak Autumn Glow

Brunette Pinstripe English Oak Harvest Cherry

White

Optional Thermofoil inset designer paneling:

Kasei Maple Mahogany

Sakura Cherry Sienna Wild Apple

Car gate type: Accordion solid panels (std)

Accordion gate with 2 clear panels (opt)

Accordion gate with all clear panels (opt)

Car gate color: Antique White (std) Black (std)

Cherry (std) Light Oak (std)

Walnut (std) Birch (std)

Chalk (std) Dark Oak (std)

Mahogany (std) White (std)

Automatic gate operator (opt): Qty: _____

Automatic door operator (opt): Qty: _____

Cab fixture package (includes COP, handrail, & hall stations):

Standard fixtures Flat fixtures (opt)

Brushed SS (std) Brushed brass (std)

Mirror SS (opt) Mirror Brass (opt)

Oil Rubbed (opt)

Phone Box: Recessed box (std) No box

Handrail: Metal Wood Additional Handrail

Job site voltage (must supply between 200 - 256 single phase VAC!):

230 VAC single phase (std) Other: _____

Other options:

Hall station key switch Pocketed gates

Automatic floor homing, select floor: _____

Remote elevator controller (within 50' of drive motor)

Speed other than 40 fpm

Hoistway wiring trough

Please insert your job conditions here:

